

GOAL ZERO LIGHTHOUSE LANTERN

LIGHTHOUSE 600 LANTERN & USB POWER HUB

Goal Zero Lighthouse 600 Lantern & USB power HUB

We've upgraded our best-selling lantern to provide 600 lumens of multi-directional, adjustable light. Packed with unique features, the Lighthouse 600 adapts to light up any situation; perfect for camping, outdoor events, or emergency use. Complete with an internal lithium battery, the Lighthouse even doubles as a power hub for charging phones and small USB devices.

Bright Light Anytime, Anywhere

Directional and adjustable LED light, up to 600 lumens. Recharge the internal battery from any USB port, from the sun with a Goal Zero solar panel, or use the built-in hand crank to charge up in an emergency.

Charge Your Devices

Internal lithium battery boasts 5200 mAh with a USB output, enough power to charge phones, headlamps, tablets, and more.

Hang It, Stand It, Store it

Collapsible legs provide a stand for maximum light dispersion and fold in for convenient storage. A built-in handle allows for easy carrying and hanging.

Multi-Directional Lighting

Utilize 360 degrees of bright LED light, or save on power and extend runtimes by illuminating half the lantern.

Three Ways to Charge

From the Sun

Recharge the Lighthouse 600 from the sun by connecting a Nomad 10 solar panel to fully charge in as little as 6 hours of sunlight.

From USE

The Lighthouse 600 can be recharged from a USB source in about 6 hours

From Cranking

When you are really in a pinch, use the hand crank to get 10 minutes of light for every 1 minute of cranking.

Charge Times

- Nomad 10: 6 hrs
- USB source: 6 hrs



Contact Danimex for more information or visit www.danimex.com/goal-zero

DMX-2021-06



TECHNICAL SPECIFICATIONS

LIGHTHOUSE 600 LANTERN & USB POWER HUB TECH SPECS	
Charge times	Nomad 10: 6 hrsUSB source: 6 hrs
Ports	 USB port (output): 5V, up to 1.5A (7.5W max), regulated USB port (input): 5V, up to 1A (5W max)
Battery details	 Cell chemistry: Li-ion NMC Cell capacity: 18.7Wh (3.6V, 5200mAh) Lifecycles: hundreds of cycles Shelf-life: Charge every 3-6 months Management system: Charging and low-battery protection built-in
General	 Product SKU: 32010 Chainable: No Simultaneous Recharge & Discharge: Yes Weight: 1.1 lbs (498 g) Dimensions: 4.5 x 5 x 6.5 in (11.4 x 12.7 x 16.5 cm) Operating usage temp: 32-104 F (0-40 C) Warranty: 12 months
Light	 LED (output): 2x3W warm white LED 600 Lumens Color Temperature: 3,500 Kelvin
Runtime	 One side lit (low power) 320 hrs One side lit (high power) 5 hrs Both sides lit (low power) 180 hrs Both sides lit (high power) 2.5 hrs Hand crank: 1 W (cranking at 120 RPM) 1 minute of crank = 10 minutes of light on low



