

GOAL ZERO - PORTABLE POWER BANK VENTURE 35 POWER BANK USB-C

THE VENTURE 35

Designed with increased protection against the elements and more power than its predecessor, the new Venture 35 is ready for anything. Equipped with an upgraded IP67 rating, the 9600 mAh power bank is now dustproof and waterproof, giving you the confidence to power essential devices through any adventure, rain or shine. Charge up the Venture 35 in only three hours using the new 18W USB-C Power Delivery port and power multiple devices at once with the addition of two USB output ports.

The Venture 35 can be recharged from a USB-C (18W) source in 3 hours.

You can alos recharge the Venture 35 from the sun by connecting a compatible solar panel in about 6 hours. We recommend the Nomad 10 or Nomad 20 for the best charging experience.

Waterproof IP67 rating

Ensures protection against dust, sand and debris, and can withstand submersion up to 1 meter of water for at least 30 minutes.

Waterproof IP67 Design

Rubberized and ruggedized to withstand wet, unpredictable weather or handling mishaps during any excursion without any coverings over the ports.

New 18W USB-C Power Delivery port Provides faster charging in and out.

Fresh design

Features a protective rubber sleeve and a waterproof plug that protects your ports against the elements when not in use.

Integrated 50 lumens emergency flashlight Emergency flashlight lights up trails or hallways in a pinch.



Contact Danimex for more information or visit **www.danimex.com/goal-zero**

DMX-2021-06



TECHNICAL SPECIFICATIONS

VENTURE 35 TECH SPECS	
Charge times	 USB-C (18W): 3 Hours USB-A (2.4A): 4 Hours Nomad 5: 12-24 Hours Nomad 10: 6-12 Hours Nomad 20: 4-8 Hours
Ports	 USB-A port (output): 5V, up to 3A each (15W max), regulated USB-C port (input/output): 5-12V, up to 3A (18W max), regulated
Battery details	 Cell chemistry: Li-ion NMC Cell type: 18650 by LG chem Cell capacity: 35.52Wh (3.7V, 9600mAh) Lifecycles: Hundreds of cycles Shelf-life: Charge every 3-6 months Fuses: None Management system: Charging and low-battery protection built-in
General	 Product SKU: 22100 IP Rating: IP67 Chainable: No Weight: 10.12oz (286.9g) Dimensions: 4.4 x 2.7 x 1.1 in (11.2 x 6.8 x 2.8 cm) Operating usage temp.: 32-113F (0-45C) Certs: CE, FCC, RoHS Warranty: 12 months
Light	LED (output): 50 Lumens, white LED





