

GOAL ZERO - PORTABLE POWER BANK

VENTURE 75 POWER BANK USB-C

THE VENTURE 75

Fast-charging technology meets rugged durability. The new Venture 75 blends the best of both worlds. Our upgraded 19200 mAh power bank features an IP67 dustproof/waterproof rating and a USB-C port designed to speed up charging and streamline cable carry. Power up tablets, laptops, and other USB-C devices using the 60W USB-C Power Delivery port, then use the same port to quickly recharge the power bank in 1.5 hours. Ideal for outdoor recreation, travel, and emergency use.

The Venture 75 can be recharged from a USB-C power delivery source in as little as 1.5 hours. We recommend the Nomad 50 or Nomad 20 for the best charging experience.

You can also recharge the Venture 75 from the sun by connecting a compatible solar panel in about 6 hours.

Waterproof IP67 rating

Ensures protection against dust, sand and debris, and can withstand submersion up to 1 meter of water for at least 30 minutes.

Waterproof IP67 Design

Rubberized and ruggedized to withstand wet, unpredictable weather or handling mishaps during any excursion without any coverings over the ports.

New 60W USB-C Power Delivery port

Provides high-speed charging in and out.

Fresh design

Features a protective rubber sleeve and a waterproof plug that protects your ports against the elements when not in use.

Integrated 50 lumens emergency flashlight Lights up trails or hallways in a pinch.



Contact Danimex for more information or visit **www.danimex.com/goal-zero**

DMX-2021-06



TECHNICAL SPECIFICATIONS

VENTURE 75 TECH SPECS	
Charge times	 USB-C PD (60W): 1.5 Hours Wall Charger (45W) USB-C: 2 Hours USB-A (2.4A): 6 Hours Nomad 10: 11-22 Hours Nomad 20: 6-11 Hours Nomad 50: 6 hours
Ports	 USBA port (output): 5V, up to 3A each (15W max), regulated USBC port (input/output): 5-20V, up to 3A (60W max), regulated
Battery details	 Cell chemistry: Li-ion NMC Cell type: 18650 by LG chem Cell capacity: 71.04Wh (11.1V, 6400mAh) Single Cell Equivalent Capacity: 19200mAh @ 3.7V Pack Lithium Content: 5.76g Lifecycles: Hundreds of cycles Shelf-life: Charge every 3-6 months Fuses: None Management system: Charging and low-battery protection built-in
General	 Product SKU: 22110 IP Rating: IP67 Chainable: No Weight: 20.35oz (577g) Dimensions: 6.1 x 3.8 x 1.1 in (15.6 x 9.6 x 2.9 cm) Operating usage temp.: 32-113F (0-45C) Certs: CE< FCC, RoHS Warranty: 12 months
Light	LED (output): 50 Lumens, white LED



