

THE VENTURE JUMP

Never get stuck with a dead car battery again. Designed to revive your battery in an emergency, the new Venture Jump features an 800 amp jump starter to safely bring your vehicle back to life and get you on your way. The Venture Jump also doubles as a power bank to charge phones and USB devices in a pinch. An essential for any commuter, traveler, or off-road adventurer. Compatible with most vehicles up to 6.0L gasoline or 3.0L diesel.

Experience ultimate self-sufficiency

No more need for roadside assistance. Smart jumper cables make it safe and easy for you to jump start your vehicle battery on your own.

All-in-one emergency essential

Integrated LED light illuminates the scene while the 10,000 mAh power bank lets you charge phones and other USB devices on-the-go.

Built to withstand the elements

IP67 rating ensures protection against dust, sand and debris, and can withstand submersion up to 1 meter of water for at least 30 minutes.

Compact and convenient

Includes protective carrying case with pockets for convenient, tangle-free cable storage.





Contact Danimex for more information or visit **www.danimex.com/goal-zero**

DMX-2022-01



Danimex Communication A/S Elholm 4 • DK-6400 Sønderborg • Denmark Phone: +45 7342 5600 • Fax: +45 7342 5615 • danimex@danimex.com • www.danimex.com

TECHNICAL SPECIFICATIONS

VENTURE JUMP SPECS	
Charge times	 USB-C (18W): 3 Hours USB-A (2.4A): 4 Hours Nomad 5: 12-24 Hours Nomad 10: 6-12 Hours Nomad 20: 4-8 Hours
Ports	 USBA 1 port (output): 5V, up to 2.1A (10.5W max), regulated USBA 2 port (output): 5V/2.1A, 9V/2A, 12V/1.5A (18W max), regulated USBC port (input): 5-9V, up to 2A (18W max), regulated Jump Starter: 12V, 400A starting (800A peak)
Battery details	 Cell chemistry: Li-ion Polymer Cell capacity: 37Wh (14.8V, 2500mAh) Single Cell Equivalent Capacity: 10000mAh @ 3.7V Lifecycles: Hundreds of cycles Shelf-life: Charge every 3-6 months Fuses: None Management system: Charging and low-battery protection built-in
General	 Product SKU: 50000 IP Rating: IP67 Chainable: No Weight (without jumper cable): 17.52oz (497g) Weight (with jumper cable): 24.28oz (688g) Dimensions: 7.1 x 3.9 x 1.5 in (18.1 x 10 x 3.8 cm) Jumper Cable: 14.5 in 10AWG Operating usage temp: -13 - 140F (-25 - 60C) Certs: CE FCC RoHS Warranty: 12 months
Light	LED (output): 45 Lumens, white LED



